C 150

Ice Cube



Modular ice maker - Sprayer system
Daily production up to 160 kg

- Hotel
- Restaurant
- Fast food
- Bar
- Disco
- Fish market
- Supermarket
- Medical & SPA
- Industry

▶ Position n°



▶ Features & Plus

- Compact and crystal cube
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Removable and cleanable air filter
- Air or water cooling system
- Easy cleanable internal rounded surfaces
- RoHS Free
- Electromechanical operation
- ON-OFF rocker switch
- Standard and special voltages



AISI 304 SS
Scotch Brite finish




Removable and
cleanable air filter

▶ Usable Bins

- Bin 240PE
- Bin 200
- Bin 350

▶ Available ice cube size



▶ Prod. 24h

Air temp.		Water temp.		Kg	Lbs
10° C	45° F	7° C	50° F	160	353
21° C	70° F	15° C	60° F	155	342

2 Years Warranty
subject to limitations

▶ Certifications available for this model

www.bremagroup.it
info@bremaicegroup.it


We are Brema

Ice Cube

C 150

BREMA

Modular ice maker - Sprayer system
Daily production up to 160 kg



▶ Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

▶ Performances

Air temperature	Water temperature 7° C	45° F	15° C	60° F	21° C	70° F
10° C	160 kg					
50° F		353 lbs				
21° C			155 kg			
70° F				342 lbs		
32° C					132 kg	
90° F						291 lbs

▶ Connections

All measures are referred to the down-left corner (L-H-Ø)

① Water in.: 129 mm / 5 1/16" - 183 mm / 7 3/16" 3/4"
② Cond. water in.: 74 mm / 2 15/16" - 143 mm / 5 10/16" - 3/4"
③ Water out.: 65 mm / 2 9/16" - 285 mm / 11 4/16" - 24 mm / 15/16"
④ Electrical connections: 129 mm / 5 1/16" - 263 mm / 10 6/16"

▶ Technical information

Production in 24h	155 kg / 342 lbs
Cooling system	A - W
Kind of cube	A-18g, C-33g, D-13g, E-42g, B-60g
Refrigerant	R452A
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	1400 W
Fuse	16 A
Finish	AISI 304 stainless steel, scotch brite

Water consumption	A: 2,6 l/kg - 31,2 gal/100 lbs
	W: 13 l/kg - 155,8 gal/100 lbs
Sizes (L-P-H mm)	862 - 555 - 720
(L-P-H in)	33 15/16 - 21 14/16 - 28 6/16
Sizes with pack (L-P-H mm)	945 - 645 - 980
(L-P-H in)	37 3/16 - 25 6/16 - 38 9/16
Net weight	118 kg / 260 lbs
Gross weight	128 kg / 282 lbs

All the technical information need to be considered at the following conditions:
Standard Cube (18 g)
Ambient temperature +21° C
Water temperature +15° C
Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Rev. 03 - Issued January 2025

BREMA
www.bremagroup.it
info@bremaicegroup.it

We are Brema