G 280

Ice Flakes



Modular ice maker - Granular system
Daily production up to 320 kg


Hotel	■■■■■■□□□□
Restaurant	■■■■□□□□□□
Fast food	■□□□□□□□□□
Bar	■□□□□□□□□□
Disco	■■■■□□□□□□
Fish market	■■■■■■■□□□
Supermarket	■■■■■■■■■■
Medical & SPA	■■■■■■■■■■
Industry	■■■■■■□□□□

▶ Position n°



▶ Features & Plus

- Granular ice - 80-82% dry
- 1l (water) - 1kg (ice) - only Air cooled
- AISI 304 SS Scotch Brite finish
- Tropical class +43°C
- Specific volume 1 m^3 = 550 kg of ice
- Removable and cleanable air filter
- AISI 304 SS evaporator
- Air or water cooling system
- Easy cleanable internal rounded surfaces
- Dust-proof water basin
- RoHS Free
- Electromechanical operation
- ON-OFF rocker switch
- Rotation sensor on low speed shaft
- Automatic water charge
- Standard and special voltages
- Frame in INOX


Removable and cleanable air filter


AISI 304 SS evaporator


Dust-proof water basin


Easy cleanable internal rounded surfaces


Frame in INOX

▶ Usable Bins

- Bin 240PE
- Bin 110
- Bin 200
- Bin 350
- Roller Bin 100
- Double Roller Bin 100

▶ Prod. 24h

	Air temp.		Water temp.		Kg	Lbs
	10° C	50° F	7° C	45° F	320	705
	21° C	70° F	15° C	60° F	280	617

2 Years Warranty
subject to limitations

▶ Certifications available for this model

www.bremagroup.it
info@bremaicegroup.it

We are Brema




Ice Flakes

G 280

BREMA

Modular ice maker - Granular system
Daily production up to 320 kg



Installation

▶ Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

▶ Performances

Air temperature	7° C	45° F	15° C	60° F	21° C	70° F
10° C	320 kg					
50° F		705 lbs				
21° C			280 kg			
70° F				617 lbs		
32° C					233 kg	
90° F						514 lbs

▶ Connections

All measures are referred to the down-left corner (L-H-Ø)

① Water in.: 80,5 mm / 3 3/16" - 120 mm / 4 12/16" - 3/4"
② Cond. water in.: 479,5 mm / 18 14/16" - 260 mm / 10 4/16" - 3/4"
③ Water out.: 479,5 mm / 18 14/16" - 65 mm / 2 9/16" - 24 mm / 15/16"
④ Cond. water out.: 479,5 mm / 18 14/16" - 130 mm / 5 2/16" - 24 mm / 15/16"
⑤ Electrical connections: 67,5 mm / 2 11/16" - 290 mm / 11 7/16"
② ④ Only for water cooling systems

▶ Technical information

Production in 24h	280 kg / 617 lbs
Cooling system	A - W
Refrigerant	R452A
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	1050 W
Fuse	10 A
Water consumption	A: 1 l/kg - 12,0 gal/100 lbs
	W: 5,2 l/kg - 62,3 gal/100 lbs

Sizes (L-P-H mm)	560 - 569 - 695
(L-P-H in)	22 - 22 6/16 - 27 6/16
Sizes with pack (L-P-H mm)	645 - 645 - 910
(L-P-H in)	25 6/16 - 25 6/16 - 35 13/16
Net weight	83 kg / 183 lbs
Gross weight	93 kg / 205 lbs
Finish	AISI 304 stainless steel, scotch brite

All the technical information need to be considered at the following conditions:
Ambient temperature +21° C
Water temperature +15° C
Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Rev. 03 - Issued January 2025

BREMA
www.bremagroup.it
info@bremaicegroup.it

We are Brema