GM 2000

FROZEN SNOW

NUOVE TECNOLOGIE DEL FREDDO

Modular ice maker - Granular system
Daily production up to **1119 kg**

Position n°



Application fields

Hotel	●●●●●○○○	Fish market	●●●●●●○○
Restaurant	●●●○○○○○	Supermarket	●●●●●●●●
Fast food	●○○○○○○○	SPA	●●●●●●●●
Bar	●○○○○○○○	Medical	●●●●●●●●
Disco	●●●○○○○○	Industry	●●●●●●○○

Features & Plus

- Granular ice
- 1 m^3 = 550 kg of ice
- Low consumption (1 liter water / 1 kg ice) - aircooled vers.
- Electromechanical functionning
- Extrernal structure AISI 304 Scotch Brite
- Monoblock Stainless steel frame
- Evaporator AISI 304, auger AISI 303 made
- Air Cooling and Water Cooling systems
- Standard and special voltages
- ON-OFF switch
- Dust proof water basin
- Easy cleaning thanks to rounded surfaces
- Removable and cleanable air filter
- Rotation sensor directly on evaporator
- Conformity to RoHS directive
- Automatic water charge
- Model in Tropical Class + 43 ° C

Usable Bins

- Bin 1200DD
- DRB 1100
- DRB 2500

Prod. 24h

Air temp.	Water temp.	Prod. 24h kg
10° C	10° C	1119
21° C	15° C	1000
32° C	21° C	800

2 Years Warranty
subject to limitations

Certifications available for this model

NUOVE TECNOLOGIE DEL FREDDO
www.bremagroup.it
info@bremaicegroup.it


ECOMPANY

GM 2000

FROZEN SNOW

NUOVE TECNOLOGIE DEL FREDDO

Modular ice maker - Granular system
Daily production up to **1119 kg**



Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

Technical information

Production in 24h	1000 kg
Cooling system	A - W
Refrigerant	R452A
Standard voltage	400-415 V ~ 3N 50 Hz
Electrical consumption	2555 W
Fuse	16 A
Water consumption	A: 1 l/kg W: 5,3 l/kg
Sizes (L-P-H mm)	934 - 684 - 700
Sizes with pack (L-P-H mm)	995 - 765 - 890
Net weight	177 kg
Gross weight	207 kg
Finish	AISI 304 stainless steel, scotch brite

Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

① Water inlet:
357 mm - 115 mm - 3/4"

② Condenser water inlet:
385 mm - 241 mm - 3/4"

③ Water outlet:
336 mm - 60 mm - 24 mm

④ Electrical connections:
322 mm - 257 mm

⑤ Condenser water outlet:
381 mm - 60 mm - 24 mm

⑥ Connection to remote electric panel:
322 mm - 216 mm

②⑤ Only for water cooling systems

All the technical information must be considered at the following conditions:

Ambient temperature +21° C

Water temperature +15° C

Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice
Rev. 03 - Issued January 2025