Fronzen Dice

SL 80 R290

Frozen Qube

Self-contained ice maker - Sprayer system
Daily production up to **52 kg**

Hotel	●●●●●●●●
Restaurant	●●●●●●○○
Fast food	●●●○○○○○
Bar	●●●●●●●●
Disco	●●●●●●●●
Fish markets	○○○○○○○○
Supermarkets	○○○○○○○○
Medical & SPA	●●○○○○○○
Industry	●○○○○○○○

Hotel	●●●●●●●○
Restaurant	●●●●●●○○
Fast food	●●●○○○○○
Bar	●●●●●●●●
Disco	●●●●●●●●
Fish markets	○○○○○○○○
Supermarkets	○○○○○○○○
Medical & SPA	○○○○○○○○
Industry	○○○○○○○○



Available Drain Pump (DP) version



Available Drain Pump (DP) version

▶ Features & Plus

- Full cube, compact and crystalline
- External structure AISI 304 Scotch Brite
- Side grilles for better ventilation
- Removable side panels
- Electromechanical functionning
- Air Cooling and Water Cooling systems
- Standard and special voltages
- Insulated retractable door
- ON-OFF switch
- Cleaning system
- Internal bin insulation HCFC free
- Conformity to RoHS directive
- Easy cleaning thanks to rounded surfaces
- Model in Tropical Class + 43 °C
- External protective filter, removable, easy to clean
- Adjustable Stainless Steel feet
- Undercounter model

2 Years Warranty subject to limitations

▶ Certifications available for this model

www.ntfice.it
info@bremaicegroup.it


We are Brema Group

Frozen Dice

SL 80 R290

Frozen Qube

Self-contained ice maker - Sprayer system
Daily production up to **52 kg**




▶ Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C / +50° F	+43° C / 110° F
Water temperature	+3° C / +37° F	+32° C / +90° F
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

▶ Available ice cube size



▶ Performances

Air temperature \ Water temperature	7° C	45° F	15° C	60° F	21° C	70° F
10° C	52 kg					
50° F		115 lbs				
21° C			49 kg			
70° F				108 lbs		
32° C					42 kg	
90° F						93 lbs

▶ Connections standard version

① Water in.: 130mm / 5 2/16" - 95mm / 3 12/16" - 3/4"
② Water out.: 56m / 2 3/16" - 155mm / 6 2/16" - 24mm / 15/16"
③ Electrical connections: 95mm / 3 12/16" - 225mm/ 8 14/16"
④ Condenser woter in. (only W):
119mm / 4 11/16" - 181mm / 7 2/16"- 3/4"

* Only for water cooling systems

Connections DP version

1 Water in.: 130mm / 5 2/16" - 190mm / 7 8/16 - 3/4"
2 Water out.: 65mm / 2 9/16" - 51mm / 2" - 24mm / 15/16"
3 Electrical connection: 55mm / 2 3/16" - 231mm / 9 2/16"

All measures are referred to the rear bottom-left corner (L-H-Ø)

▶ Technical information

Production in 24h	49 kg / 108 lbs
Store capacity, up to	16 kg / 35 lbs
Cooling system	A - W
Kind of cube	14-17-32-41g, Q-23g
Refrigerant	R290
Standard voltage	220-240 V ~ 50 Hz
Average power consumption	450 W
Fuse	10 A
Electrical consumption	22 kWh/100kg

Water consumption	A: 3 l/kg - 35,9 gal/100 lbs
	W: 15 l/kg - 179,7 gal/100 lbs
Sizes (L-P-H mm)	497 - 604 - 686
(L-P-H in)	19 9/16 - 23 12/16 - 27
Sizes with pack (L-P-H mm)	550 - 660 - 860
(L-P-H in)	21 10/16 - 26 - 33 14/16
Net weight	42 kg / 93 lbs
Gross weight	48 kg / 106 lbs
Finish	Stainless steel 18/8, scotch brite

All the technical information must be considered at the following conditions:
Sizes without feet
Standard Cube (17 g)
Ambient temperature +21° C
Water temperature +15° C
Electrical consumption at +32° C (standard voltage)
Average power consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice

Rev. 00 - Issued February 2026

NTF
www.ntfice.it
info@bremaicegroup.it
We are NTF