Split 3300

FROZEN ICE

NUOVE TECNOLOGIE DEL FREDDO

Modular ice maker - Scale system
Daily production 1500 kg

Position n°



Application fields

Hotel	○	Fish market	●
Restaurant	○	Supermarket	●
Fast food	○	SPA	●
Bar	○	Medical	●
Disco	○	Industry	●

Features & Plus

- Subcooled flakes (from -5°C to -10°C)
- 1 m^3 = 430 kg of ice
- Low consumption (1 liter water / 1 kg ice)
- AISI 304 SS Scotch Brite finish
- Evaporator anticorodal alloy made, with rotating knife
- Cleanable antiscale filter
- Easy cleaning thanks to rounded surfaces
- FDA approved -ABS plastic components
- Conformity to RoHS directive
- Automatic water charge
- Standard and special voltages
- Model in Tropical Class + 43 ° C

Usable Bins

- Bin 1200DD
- DRB 1100

2 Years Warranty
subject to limitations

Certifications available for this model

NUOVE TECNOLOGIE DEL FREDDO
www.bremagroup.it
info@bremaicegroup.it


ECOMPANY

Split 3300

FROZEN ICE

NUOVE TECNOLOGIE DEL FREDDO

Modular ice maker - Scale system
Daily production 1500 kg



Working conditions

- Location: **Indoor**

	Min	Max
Ambient temperature	+10° C	+43° C
Water temperature	+3° C	+32° C
Voltage	-10%	+10%
Water inlet pressure	1bar (14 psi)	6bar (84 psi)

Technical information

Production in 24h	1500 kg
Refrigerant	R404A - R507 - R448A - R449A - R407F - R452A
Refrigerant capacity	8550 W (evap. temp. -24° C)
Standard voltage	220-240 V ~ 50 Hz
Electrical consumption	180 W
Sizes (L-P-H mm)	604 - 700 - 970
Sizes with pack (L-P-H mm)	655 - 785 - 1145
Net weight	144 kg
Gross weight	160 kg
Finish	AISI 304 stainless steel, scotch brite

Connections

All measures are referred to the rear bottom-left corner (L-H-Ø)

① Water inlet:
123 mm - 120 mm - 3/4"

② Water outlet:
78 mm - 65 mm - 24 mm

③ Electrical connection:
123 mm - 204 mm

④ Refrigerant feeding pipe

⑤ Outlet pipe of gaseous refrigerant

All the technical information must be considered at the following conditions:

Refrigerant capacity 8580 W (evap. temp. -24° C)

Water temperature +15° C

Electrical consumption at +43° C (standard voltage)

Models and specifications are subject to change without notice
Rev. 03 - Issued January 2025